



**General Notes**

Decorative Door Plant-Ons are allowed on 20, 45, 60 and 90 minute labeled fire doors. The following conditions apply:

1. Type, size and configuration are limited by the door manufacturer's tested authorities.
2. The plant-ons must be applied under label service at factory or qualified distributor. Plant-ons may not be field applied to fire rated doors.

**Profiles offered by GRAHAM:**

GRAHAM offers the following profiles. Customers may supply assembled plant-ons in other species and profiles, provided they meet the specifications for the intended use listed below. These may also be used on non-fire rated doors.

Specifications	20 Minute	GP 45/60 Minute	GP 90 Minute
Max. Profile Width:	1-3/4"	2-1/2"	2-1/2"
Max. Profile Height	3/4"	3/4"	3/4"
Wood Specie	Douglas Fir or Denser	Same	Same
Attachment	Adhesive or Mechanical	Adhesive or Mechanical	Adhesive
Spacing: to edge of door or cutout	4"	4"	4"
Between Plant-Ons	Equal or Greater than Profile	Same	Same
Min. Enclosed Area	N/A	2 Times Profile Width & Height	2 Times Profile Width & Height
Coverage	Mouldings may not cover in excess of 20% of door face.	Mouldings may not cover in excess of 22% of door face.	Mouldings may not cover in excess of 22% of door face.